

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: HDWR

Supplier's address: Biuro obsługi klienta, Romana Dmowskiego 28, 63-000 Środa Wielkopolska Wielkopolskie, PL

Model identifier: LumixDesk-13

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	DC 5.5 × 2.1 mm		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	36	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 450 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3000...6000
On-mode power (P_{on}), expressed in W	36,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,370 0,370	
Parameters for directional light sources:				
Peak luminous intensity (cd)	770	Beam angle in degrees, or the range of beam angles that can be set	84	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	65	Survival factor	1,00	
the lumen maintenance factor	0,80			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a) '-': not applicable;

(b) '-': not applicable;



EPREL registration number: 2311915

Model placed on the Union market from 09/03/2024.



<https://eprel.ec.europa.eu/qr/2311915>

Complementary information (not part of the compliance assessment):

GTIN identifier: 5907614668983

Supplier: HDWR Global spółka z ograniczoną odpowiedzialnością (Importer) **Website:** <https://hdwrglobal.com/>

Customer care service:

Name: Biuro obsługi klienta

Website: hdwrglobal.com

Email: biuro@hdwr.pl

Phone: +48456456001

Address:

Romana Dmowskiego 28
63-000 Środa Wielkopolska
Poland